

PUMPING STATIONS IN POLYETHYLENE

WITH 1 PUMP, VERY SMALL FLOW RATES, CLEAN WATER

- Available in a 100 litre tank.
- Equipped with Pedrollo TOP 1
- Suitable for rainwater without pollution, such as emptying sellers, pools, ...
- Exclusive alarm
- Equipped with non-return valve
- Maximum discharge head 6 meter—Maximum flow rate 160 L/min



WITH 1 OR 2 PUMP(S), SMALL FLOW RATES, CLEAN WATER

- Available in a 850 litre tank.
- Equipped with pump(s) Pedrollo TOP 2 and TOP 5
- Suitable for rainwater without pollution, such as emptying sellers, pools, ...
- Including control unit and alarm
- Equipped with sieve basket at the inlet.
- Equipped with non-return valve
- Maximum discharge head 14 meter—Maximum flow rate 400 L/min






WITH 1 OR 2 PUMP(S), SMALL FLOW RATES, WASTEWATER

- Available in a 850 litre tank.
- Equipped with pumps RXm2/20, RXm 5/40, MCM10/45 and MCM15/45
- Suitable for rainwater with small pollution, such as mud in emptying building sellers, water after a water treatment plant, ...
- Including control unit and alarm
- Equipped with sieve basket at the inlet
- Equipped with non-return valve
- Maximum discharge head 12 meter—Maximum flow rate 380 L/min



WITH 1 OR 2 PUMP(S), SMALL FLOW RATES, WASTEWATER WITH GRINDER

- Available in a 850 litre tank.
- Equipped with pump(s) Pedrollo TRITUS TRm
- Suitable for sewage water with larger particles, such as fecal water from houses or after a septic tank, ...
- Including control unit and alarm
- Equipped with sieve basket at the inlet
- Equipped with non-return valve
- Maximum discharge head 23 meter—Maximum flow rate 120 L/min



Boralit NV—Version 2017

Nijverheidslaan 12, BE 9880 Aalter—Belgium—2016

Tel: +32 (0)9 375 11 11 Fax: +32 (0)9 375 22 22

E-mail: sales@boralit.be

www.boralit.com

BORALIT

plastic tank solutions