



ABOVE GROUND MULTI PURPOSE TANKS



Table of contents

Earn money with rainwater	3
Field of application	3
Options	5
Installation requirements	6
Maintenance	6
Warranty	6
Other documents	6

The published rates are exclusive of VAT, and ex works.



EARN MONEY ON RAINWATER.

Boralit has a range of above round rainwater tanks Multi purpose (1.100 to 4.000 litres).

These tanks are equipped with warm galvanized reinforcements, a hermetic screw lid, and depending on the volume 1 (1100 and 1500 liter) or 3 (2000 up to 4000 liter) 2"- F on top of the tank.

At the lower part of the tank, we can install a 2" F connection.

There are kits available to connect tanks with the same volume.

FIELD OF APPLICATION:

These tanks can be used for all kinds of fields.

They are for the storage of the following products:

- Rainwater
- Additives for concrete
- Used printing ink,
- ...

The prices of the tanks and options mentioned are for these purpose.

They can also be used for the following applications:

- Septic tank
- Water treatment
- Mud trap
- Grease separator
- Hydrocarbon separator
- ...

There are other prices for these applications..

Please contact us for further information.

Above ground multi purpose tanks

Available in – 1.100, 1.500, 2.000, 2.500, 3.000 and 4.000 liter.

OP1100



Installation above ground	
Color	White
Volume	1.100 liter
Length	1.400 mm
Width	720 mm
Height	1.400 mm
Diameter manhole	400 mm
Weight	55 kg
Price – G01	
<small>Dimensions are in mm and informative. Subject to alterations.</small>	

OP1500



Installation above ground	
Color	White
Volume	1.500 liter
Length	1.540 mm
Width	720 mm
Height	1.625 mm
Diameter manhole	400 mm
Weight	80 kg
Price – G01	
<small>Dimensions are in mm and informative. Subject to alterations.</small>	

OP2000



Installation above ground	
Color	White
Volume	2.000 liter
Length	2.070 mm
Width	720 mm
Height	1.690 mm
Diameter manhole	400 mm
Weight	110 kg
Price – G01	
<small>Dimensions are in mm and informative. Subject to alterations.</small>	

OP2500



Installation above ground	
Color	White
Volume	2.500 liter
Length	1.870 mm
Width	995 mm
Height	1.650 mm
Diameter manhole	400 mm
Weight	115 kg
Price – G01	
<small>Dimensions are in mm and informative. Subject to alterations.</small>	

OP3000



Installation above ground	
Color	White
Volume	3.000 liter
Length	2.230 mm
Width	995 mm
Height	1.650 mm
Diameter manhole	400 mm
Weight	165 kg
Price – G01	
<small>Dimensions are in mm and informative. Subject to alterations.</small>	

OP4000



Installation above ground	
Color	White
Volume	4.000 liter
Length	2.430 mm
Width	995 mm
Height	1.950 mm
Diameter manhole	400 mm
Weight	235 kg
Price – G01	
<small>Dimensions are in mm and informative. Subject to alterations.</small>	

Options

Part	Price – G01
In or out 110 mm	
In or out 125 mm	
Flange 2"	
Basic set excl tap	
Extension set excl tap	
Basic set incl tap	
Extension set incl tap	



INSTALLATION PROCEDURES, MAINTENANCE AND WARRANTY

The client acknowledges to have received a copy of this and agrees.
The installation requirements should be read FIRST BEFORE placement.

In the event of loss by the customer of the installation requirements the customer must always ask for a new copy of the installation requirements at Boralit nv, or download them from the Boralit Web site.

INSTALLATION PROCEDURES

These tanks will only resist UV rays for a few years. Therefore, when these tanks are installed in open air, we strongly recommend providing a shelter for protection. Install the tank on a stable (concrete, tiles, brick floor, ...) flat and horizontal positioned (maximum angle of 1% allowed) surface. Make sure this surface is at least 10 cm longer and wider than the tank itself. Never put tanks on sharp objects such as e.g. gravel. Never install the tank close to a heat source (the tanks are fire class F). Make sure there is a distance of at least 10 cm between the tank and any wall that should be in the proximity of the tank. Always treat the tank carefully (especially in case of frost). Avoid jolts or shocks.

MAINTENANCE

The maintenance will depend on the use..

WARRANTY

We offer a 10-year warranty on all our tank products as far as evident manufacturing faults are concerned. Failure to comply with installation procedures and guidelines voids warranty.
2-year warranty on all parts.

The general sales and warranty conditions of Boralit count.

OTHER DOCUMENTS

These documents are also available:

- Manual for the connection of Multi purpose tanks.